



DASH XD



RESIDENTIAL

DASH XD

LIMITED
WARRANTY
2
YEAR
200
HOURS
RESIDENTIAL

FABRICATED FRAME FOR DURABILITY

1"x 2" fabricated steel frame making it tough and durable.

FOOT-OPERATED DECK LIFT

Easily adjust the deck height between 1.5"-4.5" with your foot.

WELDED FABRICATED STEEL DECK

11 GA welded fabricated steel deck adds durability compared to a stamped deck.

COMPACT SIZE

Easily fits through most gates to tackle fenced-in back yards. The small footprint makes it ideal for storing in a garage.

SMOOTHTRAK™ STEERING

Developed over decades of experience. Precision control designed to help trim and maneuver easily around obstacles.

BOLSTERED SEAT

Bolstered with built-in lumbar support.

KAWASAKI® POWER

V-Twin Kawasaki engine

STANDARD ENGINE GUARD



DECK SIZE / ENGINE

34"	15 HP*	Kawasaki® FR541
42"	15 HP*	Kawasaki® FR541
48"	18 HP*	Kawasaki® FR600

MORE FEATURES



PREMIUM SEAT

Bolstered with built-in lumbar support.



PREMIUM POWER

V-Twin Kawasaki® engine.



18" REAR DRIVE TIRES

ACCESSORIES

(Each sold separately)

- Mulch kit
- Grass bagger
(non-powered 5.4 bushels, X, XL, XD)
- Steering lever extension kit
- Light kit
- Armrest kit
- Stripe kit



DASH XD[®]

ENGINE	
Manufacturer	Kawasaki [®] FR series
HP	34" & 42" deck: 15 HP—FR541 • 48" deck: 18 HP—FR600 (Per SAE J1995)
Displacement	603 cc
DRIVE SYSTEM	
Type	Dual hydrostatic
Transmission	Hydro-Gear ZT-1800 [®]
Speed	Up to 6 MPH
Parking Breaks	Integrated with steering levers
DECKS	
Cutting Width	Side discharge: 34", 42", 48"
Cutting Heights	1.5"–4.5"
Deck Lift	Foot operated
Depth	4.1"
Blades	34" & 42": 2 • 48": 3
Blade Length	34": 16.75" • 42": 20.50" • 48": 16.5"
Blade Tip Speed	34": 17,500 • 42": 16,700 • 48": 17,200
Spindles	Aluminum with 3/4" shafts and triple protection sealed ball bearings
Drive	Electric PTO clutch
Construction	Fabricated 11 GA steel
Spindle Mounts	Reinforced 14 GA steel
Impact/Trim Areas	1/4" x 3/4" steel bar
CONSTRUCTION	
Frame	1" x 2" steel tubing
Front Axle	Fabricated with sealed ball bearings
Front Caster Wheels	Sealed ball bearings
Front Caster Forks	Fabricated 1/4" steel
GENERAL	
Seat	Premium bolstered seat with built-in lumbar support
Fuel Capacity	2 gallons
Cupholder	Yes
Front Tire	11 x 4
Drive Tire	34": 18 x 6.5–8 • 42", 48": 18 x 8.5–8
DIMENSIONS	
Weight	34" deck: 455 lbs 42" deck: 467 lbs 48" deck: 490 lbs
Height	40"
Length	65.4"
Width w/Chute Up	34": 37.5" 42": 43.25" 48": 48.25"
Tire Width	34": 35" 42", 48": 41"
Trim Side	34": 0.4" 42": 0.3" 48" 4.1"
PRODUCTIVITY*	
Acres Per Hour	34": 1.65 42": 2.04 48": 2.33

Specifications are subject to change without notice.

* Number based on 80% efficiency. This rating is to account for actual mowing conditions including overlapping, turning and terrain.

** Specifications are subject to change without notice.

† Guidance and recommendations based on total property size and will vary depending on yard and terrain conditions. See your local dealer for expert advice.